



[11] Patent Number: 6,081,491

[45] **Date of Patent:** Jun. 27, 2000

[56] References Cited

U.S. PATENT DOCUMENTS

4,530,018	7/1985	Hoshino et al. .	
4,750,059	6/1988	Syracuse .	
5,434,829	7/1995	Maeda et al.	369/54 X
5,636,193	6/1997	Ohmi .	
5,706,265	1/1998	Bang	369/47 X

FOREIGN PATENT DOCUMENTS

07182796 7/1995 Japan .

Primary Examiner—Paul W. Huber

Attorney, Agent, or Firm—Akin, Gump, Strauss, Hauer & Feld, L.L.P.

Related U.S. Application Data

[57] ABSTRACT

[30] Foreign Application Priority Data

In an optical disk reproducing device capable of rotating an optical disk at a selected one of a plurality of preset linear velocities, vibration or shock of the device is detected during rotation of the disk, and the linear velocity of the disk is determined based on the result of the detection of the vibration or shock to restrain the vibration and shock within a permissible range. A limit rotational velocity above which the vibration or shock is excessive may be determined during a test conducted each time a disk is inserted, and the linear velocity of the disk during reproduction may be determined such that the rotational velocity does not exceed the limit rotational velocity.

11 Claims, 3 Drawing Sheets

[58] **Field of Search** 369/32, 33, 47,

369/48, 50, 53, 54, 58, 44.27, 44.28, 44.29,
44.32; 360/73.03

